




















Part Number	RF4-IH-6993-32309-3	RF4-IH-6C19-32309-3	RF4-IV-83634-16309-3
Series	I - Series	I - Series	I - Series
Socket Type	GB2099.3 	IEC 320 C19 standard (right) 	BS 1363 (45degree) 
Socket Quantity	6	6	8
Power Input	Back input	Back input	Back input
Bracket Install	Frontal installation	Frontal installation	Inverse installation
Cable with plug	IEC60309 plug (32A 2P+E) 	IEC60309 plug (32A 2P+E) 	IEC60309 plug (16A 2P+E) 
Control Function	No controlling function	No controlling function	No controlling function
Protection Function	No protecting function	No protecting function	No protecting function
Case	Black	Black	Black
Cable Specification	3 x 6.0 mm ² x 3M	3 x 6.0 mm ² x 3M	3 x 2.5 mm ² x 3M
Product Size (L x W x H)	483.8 x 44.4 x 62 mm	484 x 44.4 x 44.4 mm	687x 44.4x 62 mm
Mounting Length	455.8 mm	463 mm	661 mm
Case Length	427.8 mm	431 mm	631 mm
PDU Exponent	1.031	0.257	1.225
Fittings	None	2pcs $\phi 6$ x16mm cross bolt 2pcs M6 float nut	2pcs $\phi 6$ x16mm cross bolt, 2pcs M6 float nut
Rating voltage	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz
Rating Current	13A	13A	13A
Max. Power	8000W	8000W	4000W
Socket assemble	None	None	None
Interior Connection Wire	2.5 mm ² (14AWG)	2.5 mm ² (14AWG)	1.5 mm ² (16AWG)
Interior Connection Style	Group connection	Standard connection	Standard connection
Fix the Cable	Cable clamp(19)	Cable clamp(19)	Cable clamp (11)

Part Number	RF4-IV-8363-16309-3	RF4-IH-8C13-16309C-3	RF4-IV-103634-16309-3
Series	I - Series	I - Series	I - Series
Socket Type	BS 1363 	IEC320 C13 	BS 1363 (45degree) 
Socket Quantity	8	8	10
Power Input	Left end single input	Left end single input	Left end single input
Bracket Install	Inverse installation	Frontal installation	Inverse installation
Cable with plug	IEC60309 plug (16A 2P+E) 	IEC60309 plug (16A 2P+E) 	IEC60309 plug (16A 2P+E) 
Control Function	No controlling function	Master air circuit breaker	No controlling function
Protection Function	No protecting function	No protecting function	No protecting function
Case	Black	Black	Black
Cable Specification	3 x 2.5 mm ² x 3M	3 x 2.5 mm ² x 3M	3 x 2.5 mm ² x 3M
Product Size (L x W x H)	547 x 44.4 x 62 mm	482.5 x 44.4 x 44.4 mm	765 x 44.4 x 62 mm
Mounting Length	521 mm	461.5 mm	739 mm
Case Length	491 mm	429.5 mm	709 mm
PDU Exponent	1.225	0.663	1.467
Fittings	2pcs Φ 6x16mm cross bolt 2pcs M6 float nut	2pcs ϕ 6 x16mm cross bolt 2pcs M6 float nut	2pcs ϕ 6x16mm cross bolt, 2pcs M6 float nut
Rating voltage	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz
Rating Current	16A	16A	16A
Max. Power	4000W	8000W	4000W
Socket assemble	None	None	None
Interior Connection Wire	1.5 mm ² (16AWG)	1.5 mm ² (16AWG)	2.5 mm ² (14AWG)
Interior Connection Style	Standard connection	Standard connection	Standard connection
Fix the Cable	Cable clamp (11)	Small cable clamp	Cable clamp (11)

Part Number	RF 4-IV-1236313-32309-3	RF 4-IV-123634-16309-3	RF 4-IV-12C132C19-16320-3
Series	I- Series	I- Series	I- Series
Socket Type	BS 1363 (135degree) 	BS 1363 45 degree 	IEC320 C13 (right) IEC 320 C19 standard (right) 
Socket Quantity	12	12	14 (IEC320 C13 - 12 Nos & IEC 320 C19 standard - 2 Nos)
Power Input	Left end single input	Left end single input	Left end single input
Bracket Install	Inverse installation	Inverse installation	Inverse installation
Cable with plug	IEC60309 Plug (32A 2P+E) 	IEC60309 Plug (32A 2P+E) 	IEC320 C20 16A Plug 
Control Function	No controlling function	No controlling function	No controlling function
Protection Function	No protecting function	No protecting function	No protecting function
Case	Black	Black	Black
Cable Specification	3 x 6.0 mm ² x 3M	3 x 2.5 mm ² x 3M	3 x 1.5 mm ² x 3M
Product Size (L x W x H)	547 x 44.4 x 62 mm	482.5 x 44.4 x 44.4 mm	765 x 44.4 x 62 mm
Mounting Length	832 mm	886 mm	613 mm
Case Length	804 mm	856 mm	581 mm
PDU Exponent	1.709	1.709	0.953
Fittings	2pcs $\phi 6$ x16mm cross bolt 2pcs M6 float nut	2pcs $\phi 6$ x16mm cross bolt 2pcs M6 float nut	2pcs $\phi 6$ x16mm cross bolt, 2pcs M6 float nut
Rating voltage	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz
Rating Current	32A	16A	16A
Max. Power	8000W	4000W	4000W
Socket assemble	None	None	None
Interior Connection Wire	2.5 mm ² (14AWG)	1.5 mm ² (16AWG)	1.5 mm ² (16AWG)
Interior Connection Style	Group connection	Standard connection	Standard connection
Fix the Cable	Cable clamp(19)	Cable clamp(11)	Cable clamp(11)

Part Number	RF4-IV-12C13-32309C-3	RF4-IH-12C13-32309-3	RF4-IV-123634-32309-3
Series	I-Series	I-Series	I-Series
Socket Type	IEC320 C13 	IEC320 C13 	BS 1363 45 degree 
Socket Quantity	12	12	12
Power Input	Left end single input	Left end single input	Left end single input
Bracket Install	Inverse installation	Frontal installation	Inverse installation
Cable with plug	IEC60309 plug (32A 2P+E) 	IEC60309 plug (32A 2P+E) 	IEC60309 plug (32A 2P+E) 
Control Function	1P 16A Master air circuit breaker (2pcs)	No controlling function	No controlling function
Protection Function	No protecting function	No protecting function	No protecting function
Case	Black	Black	Black
Cable Specification	3 x 6.0 mm ² x 3M	3 x 6.0 mm ² x 3M	3 x 6.0 mm ² x 3M
Product Size (L x W x H)	861 x 44.4 x 62 mm	486 x 44.4 x 44.4 mm	912 x 44.4 x 62 mm
Mounting Length	835 mm	465 mm	886 mm
Case Length	805 mm	433 mm	856 mm
PDU Exponent	1.064	0.725	1.709
Fittings	2pcs ϕ 6 x16mm cross bolt 2pcs M6 float nut	2pcs ϕ 6 x16mm cross bolt 2pcs M6 float nut	2pcs ϕ 6x16mm cross bolt, 2pcs M6 float nut
Rating voltage	250VAC 50/60Hz	250VAC 50/60Hz	250VAC 50/60Hz
Rating Current	32A	32A	32A
Max. Power	8000W	8000W	8000W
Socket assemble	None	None	None
Interior Connection Wire	2.5 mm ² (14AWG)	2.5 mm ² (14AWG)	2.5 mm ² (14AWG)
Interior Connection Style	Standard connection	Standard connection	Standard connection
Fix the Cable	Cable clamp(19)	Cable clamp(19)	Cable clamp(11)